



Modular Acoustic Enclosure

S450-1 - S550-1 Scania Range

Developed through continuing research and development by our specialist engineers, all FG Wilson enclosures are fully weatherproof and incorporate internally mounted exhaust silencers. Designed on modular principles, they have interchangeable components permitting on-site repair. Extremely durable and robust, the enclosures are designed to resist corrosion and handling damage with the ability to withstand rough handling common on many construction sites.

Durable and Robust Construction

- High grade steel protected by power coat paint
- Black finish stainless steel locks and hinges
- Zinc plated or stainless steel fasteners

Excellent Access for Maintenance

- Large side hinged doors on both sides of enclosure providing optimal access
- Radiator fill access plate
- Lube oil and cooling water drains piped to exterior of the enclosure


Security and Safety


- Control panel viewing window in a lockable access door
- Emergency stop push button (red) mounted on enclosure exterior
- Cooling fan and battery charging alternator fully guarded
- Fuel fill and battery can only be reached via lockable access doors
- Exhaust silencing system totally enclosed for operator safety

Transportability

- Optional tested and certified lifting arch
- Lifting points on baseframe

Sound Pressure Levels (dBA) for 410 - 550 kVA CAE Enclosure 60 Hz 15m (50ft) 7m (23ft) 1.5m (4.5 ft) 1m (3ft) 100% Load 75% Load 100% Load Generator Set Model 75% Load 100% Load 75% Load 100% Load 75% Load 66.8 68.0 72.8 74.0 81.2 81.6 85.2 84.7 Prime S450-1 67.1 68.5 73.1 74.5 81.3 81.9 84.8 85.4 Standby 67.5 69.3 73.5 75.3 81.5 82.3 85.0 85.8 Prime S550-1 68.0 70.1 74.0 76.1 81.7 82.7 85.2 86.3 Standby





Dimensions and Weights								
Generating Set	A:	B:	C:	D:	E*:	F*:	Weight:	Fuel Capacity
Model	mm (in)	mm (in)	mm (in)	mm (in)	mm (in)	mm (in)	kg (lb)	l (US gal)
S450-1	4560 (179.5)	1600 (63.0)	2198 (86.5)	2138 (84.2)	1000 (39.4)	1010 (39.8)	4325 (9535)	250 (66.0)
S550-1	4560 (179.5)	1600 (63.0)	2198 (86.5)	2138 (84.2)	1000 (39.4)	1010 (39.8)	4325 (9535)	250 (66.0)

Weight with lube oil and coolant, no fuel; *Clearance required on both sides and at end.

FG Wilson manufactures product in the following locations:

Northern Ireland • Brazil • China • India • USA

With headquarters in Northern Ireland, FG Wilson operates through a Global Dealer Network. To contact your local Sales Office please visit the FG Wilson website at www.FGWilson.com.

FG Wilson is a trading name of Caterpillar (NI) Limited.